



LAN CABLE CAT6

MODELO CAT6-UTP-C

- Reference standard: ANSI/TIA 568C & YD/T1019
- Application: For network cabling systems, including 10/100/1000 Base-T, performance to meet the standard requirements.
- Rated voltage:30V

Construction		
1.Conductor (mm)	Solid bare copper 0.57+/-0.01	
2.Insulation (mm)	HDPE 1.02±0.08	
3.Color Code	White-Blue (Stripe)/Blue White-Orange(Stripe)/Orange White-Green(Stripe)/Green White-Brown (Stripe)/Brown	
4.Wrapping (mm)	----	
5.Screen (mm)	----	
6.Drain wire (mm)	----	
7.Cross	Yes	
8.Rip cord	630D	
9.Jacket (mm)	Material	LSZH
	Nom.thickness	0.5
	Color	Multiple
	Nom.diameter	6.0±0.3
Printing	According to customer	



Mechanical characteristics

Operating temperature	-20~75°C
Installation temperature	0~75°C
Tensile strength.Max	80N
Bending radius	8D
Flame resistant	----
Length of Delivery	305m/box
Net.weight	11.5kg
Gross.weight	12.3kg

Electrical characteristics (20°C)

Conductor resistance .Max	9.5Ω/100m
Conductor resistance unbalance .Max	2.5%
Insulation resistance(DC 500V/1 min) .Min	5000MΩ·km
Dielectric strength (C-C, .DC.1min)	1kV
Mutual capacitance .Max	5.6nF/100m

Frequency (MHz)	Attenuation (dB)	NEXT (dB)	PSNEXT (dB)	ELFEXT (dB)	PSELFEXT (dB)	Delay (ns)	Return Loss (dB)
1	2.0	74.3	72.3	67.8	64.8	570.0	20.0
4	3.8	65.3	63.3	55.8	52.8	552.0	23.0
8	5.3	60.8	58.8	49.7	46.7	546.7	24.5
10	6.0	59.3	57.3	47.8	44.8	545.4	25.0
16	7.6	56.2	54.2	43.7	40.7	543.0	25.0
20	8.5	54.8	52.8	41.8	38.8	542.0	25.0
25	9.5	53.3	51.3	39.8	36.8	541.2	24.3
31.25	10.7	51.9	49.9	37.9	34.9	540.4	23.6
62.5	15.4	47.4	45.4	31.9	28.9	538.6	21.5
100	19.8	44.3	42.3	27.8	24.8	537.6	20.1
200	29.0	39.8	37.8	21.8	18.8	536.5	18.0
250	32.8	38.3	36.3	19.8	16.8	536.3	17.3