

NAP NEGRA 2 IN 16H CON SC/APC Y PLC 1*16

MODELO PB-0216C




PRODUCT DESCRIPTION

PB-0216C Fiber optic distribution box is able to hold up to 16 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

ITEM	FIBER OPTIC DISTRIBUTION BOX
MODEL NO.	PB-0216C
DESCRIPTION	Accommodated 16 SC/APC Adapters

FEATURES


1. Water-proof design with IP-66 Protection level.
2. Integrated with splice cassette and cable management rods.
3. Manage fibers in a reasonable fiber radius condition.
4. Easy to maintain and extend the capacity.
5. Fiber bend radius control more than 40mm.
6. Suitable for the fusion splice or mechanical splice.
7. 1*16 Splitter can be installed as an option.
8. Efficient cable management.
9. 16 ports cable entrance for drop cable.




Pic 1 Box Size



Pic 2 Installation Size



Wall mounted installation



Pole ring installation

STANDARD ACCESSORIES

Splice cassette and cable management tool, installation nuts and bolts, protection sleeves, hose clamp, rubber seal for cable entrance.

Optional Accessories

Pole ring, Extra lock and key

Item	Size(A*B*C)	Installation Size (D*E)	Max Capacity		
			SC 16 Core	LC 16 Core	PLC 1*16(sc)
PB-0216C	292*218*83mm	154*82mm			