

ROSETA 1 SC/APC 120*90MM

MODELO TPB-01



DESCRIPTION

This box is used as a termination point for the feeder cable to connect with drop cable in FTTX communication network system.

It integrates fiber splicing, splitting, distribution, storage and cable connection in one unit. Meanwhile, it provides solid protection and management for the FTTX network building.

FEATURES

1. Total enclosed structure.
2. Material: ABS, wet-proof, water-proof, dustproof, anti-aging, protection level up to IP65.
3. Clamping for feeder cable and drop cable, fiber splicing, fixation, storage distribution ... etc all in one.
4. Cable, pigtails, patch cords are running through own path without disturbing each other, cassette type SC adaptor installation, easy maintenance.

CONFIGURATION

Material	Size	Max Capacity	Nos of PLC	Nos of Adaptor	Weight	Ports
Strengthen ABS	A*B*C(mm) 120*90*24	Splice 1 Fibers (1trays, 1 core/tray)	\	1 pcs of SC(max)	0.10kg	1 ports

APPLICATIONS

- Wall mounting and pole mounting installation
- FTTH pre-installation and field installation
- 5-10mm cable ports suitable for 2x3mm indoor FTTH drop cable and outdoor figure 8 FTTH self-supporting drop cable

STANDARD ACCESSORIES

Screw: 1pcs

Expansion bolt: 1pcs

Heat-shrink sleeve: 1 pcs

