

16 Core Fiber Optic Distribution Box

Description

This box is used as a termination point for the feeder cable to connect with drop cable in FTTX communication network system.

It intergrates fiber splicing, splitting, distribution, storage and cable connection in one unit. Meanwhile, it provides solid protection and management for the FTTX network building.

Features

- 1、Total enclosed structure.
- 2、Material: ABS, wet-proof, water-proof, dust proof, anti-aging, protection level up to IP65.
- 3、Clamping for feeder cable and drop cable, fiber splicing, fixation, storage distribution ... etc all in one.
- 4、Cable, pigtails, patch cords are running through own path without disturbing each other, cassette type SC adaptor .installation, easy maintenance.
- 5、Distribution panel can be flipped up, feeder cable can be placed in a cup-joint way, easy for maintenance and installation.
- 6、Box can be installed by the way of wall-mounted or poled-mounted,suitable for both indoor and outdoor uses.



SC Type



PLC Type

Frqiljxudwlrq

P dwhuldo	VI}h	P d{ Fdsdflw	Nos of PLC	Qrv ri Dgdsrwru	Z hlj kw	Sruuv
Strengthen PP	A*B*C(mm) 290*185*120	Splice 16 Fibers (1trays, 16 fiber/tray)	2 pcs of 1x8 1 pcs of 1x16	16 pcs of SC(max)	1. 65kg	3 in 16 out

Packing List

PCS/CARTON	Gross Weight (Kg)	Net Weight (Kg)	Carton Size (cm)	Cbm (m³)
8	13.5	12.5	67*31*41	3i090

Standard Accessories

- Screw: 4mm*40mm 2pcs
- H{sdnsion bolt: M6 2pcs
- Cable tie:3mm*10mm 9sfv
- Heat-shrink sleeve:1.0mm*3mm*60mm 49sfv
- Hook:2sfv
- hoop ring 6sfv
- TPR black block 5 sfv
- Fiber protective tube: 1pcs
- Insulating tape: 1pcs

