

8 Core Fiber Optic Distribution Box

Ghvfulswlrq

The equipment is used as a termination point for the feeder cable to connect with drop cable in

FTTX communication network system. The fiber splicing, splitting, distribution can be done in this

box and meanwhile it provides solid protection and management for the FTTX network building

Features

- 1、Total enclosed structure.
- 2、Material: ABS、PC+ABS, wet-proof、 water-proof、 dust-proof、 anti-aging, protection level up to IP65.
- 3、Clamping for feeder cable and drop cable, fiber splicing, fixation, storage distribution ... etc all in one.
- 4 、 Cable, pigtails, patch cord:s are running through own path without disturbing each other, cassette type SC adaptor .installation, easy maintenance.
- 5、 Distribution panel can be flipped up, feeder cable can be placed in a cup-joint way, easy for maintenance and installation.
- 6 、 Cabinet can be installed lby the way of wall-mounted or poled-mounted,suitable for both indoor and outdoor uses.



Configuration

Material	Size	Max Capacity	Nos of PLC	Nos of Adaptor	Weight	Color
Strengthen ABS	A*B*C(mm) 190*130*46	Splice 8 Fibers (1trays,8 fiber/tray)	/	8pcs of SC(max)	0.23kg	White

Packing List

PCS/CARTON	Gross Weight (Kg)	Net Weight (Kg)	Carton Size (cm)	Cbm (m³)
53	17	46	70.5*22*53	3.078

Standard Accessories

- Screw: 4mm*40mm 4pcs
- Expansion bolt: M6 4pcs
- Cable tie:3mm*10mm 9sfv
- Heat-shrink sleeve:1.0mm*3mm*60mm 8sfv

